

Product data sheet

Specifications



SpaceLogic KNX Switch/Blind Extension 8ch 10AX/16AC1

MTN6805-0008

Main

Range of product	SpaceLogic KNX
Product or component type	Combined blind relay
Operating mode	KNX bus system
Bus type	KNX
Rated input	ON/OFF status:

Complementary

Mounting support	DIN rail
[Ue] rated operational voltage	250 V AC 50/60 Hz
[In] rated current	16 A 10 A
Number of outputs	8 4

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	366.0 g
Package 1 Height	7.7 cm
Package 1 width	12.4 cm
Package 1 Length	15.7 cm
Unit Type of Package 2	S04
Number of Units in Package 2	24
Package 2 Weight	9.596 kg
Package 2 Height	30.0 cm
Package 2 width	40.0 cm
Package 2 Length	60.0 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information