

Product data sheet

Specifications



Power supply, SpaceLogic KNX, REG-K/1280 mA, white

MTN6513-1201

Main

Range of product	SpaceLogic KNX
Product or component type	Power supply
Bus type	KNX
Topology	TP256
Provided equipment	Line choke
Colour	White

Complementary

Total number of 18 mm modules	6
Mounting support	DIN rail
Rated voltage	180...264 V AC 50...60 Hz
Maximum power consumption in W	6.4 W
Maximum short-circuit current	3 A
Maximum output current	1280 mA
Output voltage	30 V DC
Power supply type	SELV
Local signalling	LED
Connections - terminals	0.5...4 mm ² screw terminal for solid cable 0.5...4 mm ² screw terminal for stranded cable 0.5...2.5 mm ² screw terminal for stranded with sleeve cable
Height	90 mm
Width	108 mm
Depth	65 mm

Environment

Ambient air temperature for operation	-5...45 °C
Ambient air temperature for storage	-25...70 °C
Relative humidity	93 % non-condensing
Operating altitude	2000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	506.0 g
Package 1 Height	8.0 cm
Package 1 width	12.5 cm
Package 1 Length	16.0 cm
Unit Type of Package 2	S04
Number of Units in Package 2	22
Package 2 Weight	12.004 kg
Package 2 Height	30.0 cm
Package 2 width	40.0 cm
Package 2 Length	60.0 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins