

Technical Specifications

Touch S Lite Touch Panels



Touch S Lite 7" Basic



Touch S Lite 7" KNX-TP



Touch S Lite 10" Basic



Touch S Lite 10" KNX-TP

CPU	Quad Core ARM Cortex - A35 CPU @1.3GHz / Rockchip PX30 Chipset			
Memory	1GB	1GB	1GB	1GB
Hard Disk	8GB EMMC	8GB EMMC	8GB EMMC	8GB EMMC
Operating System	Android 8.1	Android 8.1	Android 8.1	Android 8.1
Power	12-30VDC	12-30VDC	12-30VDC	12-30VDC
Screen size	7"	7"	10.1"	10.1"
Resolution	600px x 1024px	600px x 1024px	1280px x 800px	1280px x 800px
Touch Panel	Projected Capacitive Touch	Projected Capacitive Touch	Projected Capacitive Touch	Projected Capacitive Touch
Microphone	1 with Echo Cancellation	1 with Echo Cancellation	1 with Echo Cancellation	1 with Echo Cancellation
Speaker	1 x 8 Ohm - 2 Watts	1 x 8 Ohm - 2 Watts	2 x 8 Ohm - 2 Watts	2 x 8 Ohm - 2 Watts
Input	5 Digital Inputs	5 Digital Inputs	5 Digital Inputs	5 Digital Inputs
Output	4 x 5A Non-Latching Relay	4 x 5A Non-Latching Relay	4 x 5A Non-Latching Relay	4 x 5A Non-Latching Relay
KNX Bus Connection	No	KNX-TP	No	KNX-TP
RS-485	1	1	1	1



Touch S Lite 7" Basic



Touch S Lite 7" KNX-TP



Touch S Lite 10" Basic



Touch S Lite 10" KNX-TP

RS-232	1	1	1	1
LAN	1	1	1	1
Wi-Fi	No	No	No	No
Dual Network Connectivity	No	No	No	No
Drivers	KNX-TP, KNX-IP, Modbus RTU, Modbus TCP, Siemens Logo			
IoT Integrations	IFTTT, Amazon Alexa, Google Home, Siri Shortcuts			
Max Accessory Limit	254	254	254	254
Max Room Limit	254	254	254	254
Intercom Standard	SIP 2.0 Peer-to-Peer			
Onwall Dimensions	140mm x 235mm x 4mm	140mm x 235mm x 4mm	264mm x 208mm x 4mm	264mm x 208mm x 4mm

